

# CATFORD ENGINEERING PRODUCTS

Phone (08) 8664 1566 Fax (08) 8664 1778  
 Web [www.catford.com.au](http://www.catford.com.au) Email [sales@catford.com.au](mailto:sales@catford.com.au)

## Two Braid, Non-skive Hydraulic Hose SAE R2AT/2SN



**Tube:** Oil resistant synthetic rubber

**Reinforcement:** Two braid of high-tensile steel wire.

**Cover:** Black, abrasion and weather resistant synthetic rubber. MSHA accepted.

**Application:** Hose range suitable to carry hydraulic fluids such as glycol, mineral oils, water, fuels, lubricants, emulsion, hydrocarbons etc, to realize the conveying of liquid and the transmission of hydraulic power.

**Working temperature:** -40°C ----- +100°C

## Two Braid of High-tensile Steel Wire Non-skive Hose

DN	Hose I.D		Wire O.D	Hose O.D	Working Pressure		Burst Pressure		Minimum Bend Radius	Weight	Length Per Roll	Price Per Roll Inc. GST
	INCH	MM	MM	MM	MPA	PSI	MPA	PSI	MM	KG/M	METRE	
6	1/4	6.4	12.7	15.0	40.0	5800	160	22840	102	0.36	50	\$315
6	1/4	6.4	12.7	15.0	40.0	5800	160	22840	102	0.36	106	\$646
10	3/8	9.5	16.7	19.0	33.1	4800	132	18840	127	0.54	50	\$385
10	3/8	9.5	16.7	19.0	33.1	4800	132	18840	127	0.54	100	\$770
13	1/2	12.7	19.8	22.2	27.6	4000	110	15720	178	0.68	52	\$489
13	1/2	12.7	19.8	22.2	27.6	4000	110	15720	178	0.68	100	\$940
16	5/8	15.9	23	25.4	25.0	3630	100	14280	203	0.8	50	\$606
19	3/4	19.0	27	29.3	21.5	3120	85	12280	241	0.94	50	\$775
25	1	25.4	34.9	38.0	16.5	2400	65	9420	305	1.35	50	\$990